



- Ø F: Flange diameter see table below
- S: thickness of flange see table below
- Ø K: Core diameter see table below
- KS: thickness of core see table below
- G: Total width = Used Width + 2 x Flange thickness
- W: Used width arbitrary, according to your requirements
- Ø AL: Axle hole from 18 to 96 mm
- Ø DL: Cable hole diameter
- R DL: Radius Cable hole
- Ø ML: Drive hole diameter
- R ML: Radius Drive hole

Product Range

The following standard components for non-returnable spools can be combined individually according to your requirements:

Flanges

Ø (mm) (d1)	Material			
	thickness (mm)	Plywood	Hard masonite	MDF
250				
300				
350	5,0		x	
400	6,0	x		
450	8,0	x		x
500	10,0	x		
600	12,0	x		x
755	15,0	x		
800	18,0	x		
900	21,0	x		
1.000	24,0	x		
1.200				
1.300				
1.400				
1.500				

Cores	Connecting elements
Material: cardboard core	Material: steel

Ø (mm) (d2)	Core Thickness (mm)							Number				
	4,0	4,5	5,0	5,5	6,0	7,0	10,0	3	4	5	6	8
100	x							x				
120	x							x				
150	x	x						x	x			
180	x	x						x	x			
200		x	x					x	x			
250			x					x	x	x	x	
312				x				x	x		x	
360					x	x			x		x	x
400					x	x	x		x		x	x
470					x	x	x				x	x

Beside these standards we are also capable to produce any dimension according to your special requirements.